

Irwindale Speedway Super Stock Rules 2020

No pretense is made for having designed a foolproof set of rules and regulations. If this rulebook does not specifically state that you can alter, change, or otherwise modify something on your car, you should consider it a violation of these rules. No part is deemed to have been approved by Irwindale Speedway by passing through prior technical inspections.

The Tech Director shall be empowered to permit reasonable and appropriate deviation from any of the specifications herein or impose any further restrictions that in his opinion do not alter the minimum acceptable requirements. Any deviation of these rules is left to the discretion of the Tech Director.

1. BODIES

- A. Any 1960 or newer sedan. No Station Wagons, Convertibles, Pick-Ups, Jeeps, etc.
- B. All cars must maintain stock OEM type body. Stock appearing fabricated door panels, rear quarter panels and deck lid allowed. No interchanging of manufacturer bodies and frames.
- C. Rear deck lid spoiler allowed maximum 5" tall and no wider than 60" wide.
- D. Steel Body car must have some stock floorboard and firewall remaining.
- E. Body must be complete – no open tail.
- F. Aftermarket LM Type bodies allowed.

2. FRAMES

- A. Full NASCAR type roll cages mandatory. Main roll bars must be a minimum of 1.75" O.D. x .090" wall steel tubing.
- B. Minimum of four (4) door bars required on both sides. Right side can be straight.
- C. Rear down bars must extend to rear cross member.
- D. Fuel cell protector required.
- E. Main roll cage uprights must be fastened to floor of uni-body cars with a minimum 3/16" thick plate, top and bottom, at all four corners. Plate must be a minimum of 4" square.
- F. Roll bar padding must be used at any point where driver may make contact.
- G. Door bars must be covered with a minimum 1/16" thick steel metal plate, top to bottom, from front and rear uprights, welded to outside of bars.

3. WINDOWS

- A. Windshield made of 1/8" thick clear polycarbonate must be used.
- B. Each car may have a rear window made of clear LEXAN.
- C. No right side window of any type is allowed.
- D. Side quarter windows can be replaced with LEXAN.
- E. Driver side window net is required and must be equipped with a quick-release device on the top front corner.
- F. Left side mirrors allowed.

4. HEIGHT, WEIGHT, AND WHEELBASE

- A. Minimum of four (4) inches of ground clearance.
- B. Minimum weight 3300 lbs with driver.
- C. Cars with OEM Steel Roof and a-post/b-post and Deduct 100#.
- D. Cars with Stock OEM Front Clip Deduct 100#.
- E. Cars using Stock Mount Shocks deduct 50#
- F. Cars using non-rebuildable shocks Deduct 25#
- G. All Cars Maximum Left Side Weight – 55%

- H. Minimum wheelbase 108" unless original chassis was manufactured at less than 108".
- I. Wheelbase must be within ½" of otherside.

5. ENGINE

- A. Ford 351 C.I.
Chevrolet 350 C.I.
Dodge 360 C.I.
Plus max .060 overbore
Maximum cubic inch 360C.I.
Maximum 10 to 1 compression.
- B. Engine must be in stock location.
- C. No "stroker" or lightweight cranks allowed. 1" Inspection hole in oil pan required.
- D. Stock cast iron heads only.
- E. Any hydraulic cam and lifter may be used.
- F. No porting or polishing will be allowed.
- G. Vortec heads are allowed.
- H. Stock steel, stock stainless steel valve train components only, 1.5 ratio roller rockers allowed.
- I. Screw in studs and guide plates allowed. No shaft mount rockers
- J. Stock stroke for engine being used, exp. 350 C.I. Chevy 3.48" stroke.

6. CARBURETOR

- A. All cars must run Holley #4412 2 barrel gauge legal carburetor.
- B. Two (2) carburetor return springs required.
- C. Maximum 1" carburetor adapter allowed.
- D. GM Factory Sealed 602 Crate Engine May Run a 4 barrel Carb.

7. AIR CLEANERS AND FILTERS

- A. No cold air box allowed. K&N air filters are allowed.

8. ENGINE LOCATION AND MOUNTS

- A. Engine oil pan height must not be less than 4".
- B. Engine setback #1 spark plug a minimum 1" ahead of upper balljoint.
- C. Crankshaft must be centered within one (1) inch of the vehicle's front frame clip.
- D. Minimum clearance between the center of the crankshaft and the ground must be 10.5" inches.

9. ELECTRICAL SYSTEM

- A. Stock HEI type ignition only. No performance after market or MSD distributors allowed.
- B. All cars must be equipped with a master electrical switch located within reach of the driver and safety crew from the both sides of the car.
- C. Batteries must be securely mounted within the confines of the body and behind the driver.
- D. Batteries must be contained in a secure container. No marine or plastic boxes allowed.

10. ENGINE COOLING SYSTEM

- A. Electric fans are permitted.
- B. Water overflow catch can unit required vented out to windshield.
- C. Water wetter permitted.

11. ENGINE EXHAUST SYSTEMS

- A. Stock manifolds are permitted.
- B. Headers are permitted. Must be 1 5/8" tube. No stepped or Tri Y's allowed.
- C. An approved muffler is mandatory, must not exceed 90 db @100 feet.
- D. Exhaust must extend past driver's compartment.

12. DRIVE TRAIN

- A. Clutch must be stock type only.
- B. Steel flywheels only.

- D. Scatter shields mandatory
- E. No lightening of flywheel permitted.
- F. Locked, limited slip, or positive-traction differentials, is permitted.
- G. Floater type rear ends are permitted.
- H. Automatic transmissions optional, torque converter must be operational.
- I. Ford 9" rear end allowed.
- J. Two (2) driveline straps within 6" of the U-Joints.
- K. Magnetic steel drive shaft must be painted white.

13. SUSPENSION AND BRAKES

- A. Stock OEM type lower control arms. Must be equal length.
- B. Tubular upper A-arms allowed.
- C. Stock OEM Spindles only. No aftermarket or tubular spindle.
- C. Stock upper control arm mounting may be moved for caster/camber.
- D. Lowering blocks allowed.
- E. All other suspension components must be of original design and origin for the chassis used.
- F. Maximum overall width (front or rear) shall not exceed 78" from outside of tire to outside of tire at spindle height with driver in the car.
- G. Steel non adjustable shocks only. Maximum retail shock price \$175.
- H. Adjustable spring spacers allowed.
- I. After market Camaro clip allowed with engine setback 1.5" behind and weight jacks.
- J. Rear disc brakes allowed.
- K. One adjustable brake bias valves allowed.
- L. Any one piece steel sway bar mounted in stock location allowed.

14. STEERING COMPONENTS

- A. Stock type steering components only.
- B. Quick release steering wheels are required.
- C. Steering column must be collapsible. Two U joints are acceptable.

15. FUEL SYSTEM

- A. Sunoco 110 or pump gas will be permitted. The chemical composition of the fuel may not be altered by any means.
- B. All cars must be equipped with an approved fuel cell mounted in the trunk area.
- C. Fuel cell must be mounted with steel framework (1 inch x 1 inch, .065 inch minimum).
- D. Fuel cell must be enclosed in a steel box. Ground strap required from fill neck to frame.
- E. Minimum fuel cell height 10" to ground. Maximum fuel capacity – 22 gallons.
- F. No electric fuel pumps permitted.

16. TIRES AND WHEELS

- A. Steel wheels are mandatory, maximum 8" width any offset.
- B. The use of any bleeder valve is prohibited.
- C. Wheel spacers allowed.
- D. The track tire is the Hoosier #970. No Star tires.
- E. At a competitors first event he/she may purchase a maximum of (4) four new tires. At each race there after he/she a maximum of (1) one new tire. You must start the race on the tires you qualify on.
- G. In the event that a competitor flattens or damages a new tire, tire must be removed and inspected by head tech official before replacement will be allowed.

17. SEATS AND SAFETY EQUIPMENT

- A. For all safety equipment. It will be the sole responsibility of the driver, not Irwindale Speedway, their agents/officials or corporate officers to ensure that his/her safety equipment is correctly installed,

maintained, and properly used. Please refer to manufacturer installation and guide lines and adhere to them.

- B. Aluminum professionally built high back racing seat required. No plastic, etc.
- C. Seat must be securely bolted to the roll cage.
- D. A five (5) point safety harness, with quick release is mandatory.
- F. Safety harnesses/seat belts may be no more than three (3) years old.
- G. Helmets; Head and Neck Restraint Devices:
 - i. Snell SA2010 or SA2015 helmet required.
 - ii. Full face helmets with Lexan face shield recommended.
 - iii. A HANS or Hutchens type head and neck restraint device is recommended.
- J. Window net mandatory.
- K. Current test date fire extinguisher to be installed in the car within drivers reach while strapped in.
- O. All cars will be required to have in their pits a minimum of one five pound fire extinguisher.

18. APPEARANCE AND IDENTIFICATION

- A. Numbers will be a minimum of 20" on the roof and both door panels.
- B. Advertising or names on the windshield is not permitted. Reserved for a series sponsor.
- C. Advertising that is deemed to be unsuitable/offensive, will not be allowed.

19. COMMUNICATION

- A. You must have a spotter stand in the spotter stand or driver must monitor race control at all times car is on track.

20. ELECTRONICS

- A. No electronic monitoring computer devices.
- B. No electronic traction control devices allowed.

2/20/20